



Shelving Selection Guide



	Industrial (pg 42-46)	Galvanized (pg 47)	Painted Wire (pg 48)	Commercial (pg 57)	Rivet (pg 64-66)
APPLICATION	All-purpose standard and heavy-duty storage.	High humidity, unheated storage; storage of solvents, oily or greasy parts.	Light industrial; for cleanliness and sprinkler access.	Commercial office, light industrial. Individual, stand alone sections.	Light industrial, record storage, commercial.
SHELF CONSTRUCTION	18, 20, 22-ga. box, 18-ga. flanged, lapped and welded.	18-ga. flanged, corners lapped and welded	Channel frame w/ ½", ¼" wire ribbing.	Dbl.-flanged at front and rear; comers lapped and welded.	Particle board with 14-ga. steel beams.
UPRIGHT CONSTRUCTION	T-Post, O.A., 16-ga. cold rolled, formed steel. Double thick.	T-Post 16-ga. cold-rolled formed steel. Double thick.	T-Post 16-ga. cold-rolled formed steel. Double thick.	Offset Angle or offset	14-ga. steel, angle or T-Post
ADJUSTABILITY	1½" centers	1½" centers	1½" centers	Offset 1½" centers	1½" centers
AVAILABLE WIDTHS	36", 42", 48"	36"	36", 48"	Offset 36, 42, 48	12"-96" in 12" increments. 69" R.S.
AVAILABLE DEPTHS	12", 18", 24"	12", 18", 24"	18", 24"	18" 24"	12", 24" - 48", in 6" increments.
AVAILABLE HEIGHTS	84", 96", 120"	84", 96", 120"	84", 96", 120"	Offset 84", 96", 120"	60", 72", 84", 96", 120"
TYPICAL SHELF CAPACITIES	600-1300 lbs.	700-800 lbs.	400-600 lbs.	600 lbs.	600-1200 lbs.
STOCK COLORS	Dove Gray, Putty, Wedgewood Blue	Shelves: Galvanized, Uprights: Gray, Putty, Blue	Dove Gray	Dove Gray, Putty	Putty

Growth Illustration Chart - 8000 Series Shelving

Growth Illustration for a 36" w x 24" d Shelving System
 Shelf dimensions: 35-13/16" w x 23-15/16" d
 Centerline of T-Posts: 36"
 Overall growth in width = 1-1/2"
 Overall growth in depth = 9/16"

